SDS Revision Date: 04/01/2020

Safety Data Sheet F-123 All Except Red, Blue, Black, Brown

Section 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Identity F-123 All Except Red, Blue, Black, Brown

Alternate Names F-123 All Except Red, Blue, Black, Brown

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name Carco, Inc

10333 ShoemakerP.O. Box 13859

Detroit, Michigan, USA 48213

Emergency

24 hour Emergency Telephone No. ChemTel 1-800-255-3924 (MIS0001475)

International +01-813-248-0585

Customer Service: Carco, Inc

Phone +1 (313) 925-9000

Fax +1 (313) 925-9602 Email: sales@carcousa.net

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Flam. Liq. 2;H225 Highly Flammable liquid and vapor. Eye Dam. 2A;H319 Causes serious eye irritation.

STOT SE 3;H336 May cause drowsiness or dizziness.

2.2. Label elements



Danger

H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

[Prevention]:

P210 Keep away from heat, sparks, open flames, and other ignition sources - No smoking.

P233 Keep container tightly closed.

P240 Ground, bond container and receiving equipment.

SDS Revision Date: 04/01/2020

Safety Data Sheet F-123 All Except Red, Blue, Black, Brown

P241 Use explosion-proof electrical, ventilating, light, equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust, fume, gas, mist, vapors, spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves, eye protection, face protection.

[Response]:

P303+361+353 IF ON SKIN (or hair): Remove, take off immediately all contaminated clothing. Rinse skin with water, shower.

P304+312 IF INHALED: Call a poison center or doctor or physician if you feel unwell.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do-continue rinsing.

P337+313 If eye irritation persists: Get medical advice or attention.

P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

[Storage]:

P403+233 Store in a well ventilated place. Keep container tightly closed.

P405 Store locked up.

[Disposal]:

P501 Dispose of contents or container in accordance with local and national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes *
1-Methoxy-2-propanol CAS Number: 0000107-98-2	25 - 50	Flam. Liq. 3;H226 STOT SE 3;H336	
Isopropyl Alcohol CAS Number: 0000067-63-0	25 - 50	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	
Titanium dioxide CAS Number: 0013463-67-7	10 - 25	Not Classified	
Rosin, Fumeric CAS Number: 800680-57-9	5 - 10	Not Classified	
Ethanol CAS Number: 0000064-17-5	5 - 10	Flam. Liq. 2;H225	
Acetic acid, 1-methylethyl ester CAS Number: 0000108-21-4	1 - 5	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	
Cellulose Nitrate CAS Number: 0009004-70-0	1 - 5	Flam. Sol. 1;H228	

In accordance with paragraph (i) of \$1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

*PBT/vPvB - PBT-substance or vPvB-substance.

The full texts of the phrases are shown in Section 16.

Section 4. First aid measures

4.1. Description of first aid measures

General In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

Inhalation Move the exposed person to fresh air at once. If not breathing, give artificial respiration. If breathing

is difficult, give oxygen. Get medical attention if any discomfort continues.

Eyes Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with

plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical

attention if any discomfort continues.

Skin Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin

cleanser.

Ingestion DO NOT INDUCE VOMITING! If swallowed, vomiting may occur spontaneously. If vomiting

occurs, keep head below hips to prevent aspiration into lungs. Rinse mouth thoroughly. Get medical

attention.

4.2. Most important symptoms and effects, both acute and delayed

Overview Treat symptomatically. Exposure to solvent vapor concentrations from the component solvents in

excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness,

drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with

possible reversible damage. See section 2 for further details.

Inhalation May cause drowsiness or dizziness.

Eyes Causes serious eye irritation.

Section 5. Fire-fighting measures

5.1. Extinguishing media

Use foam, extinguishing powder, dry chemicals, or carbon dioxide. Water may be ineffective. Water may be used to keep fire exposed containers cool.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: None

Keep away from heat, sparks, open flames, and other ignition sources - No smoking.

Keep container tightly closed.

Ground, bond container and receiving equipment.

Use explosion-proof electrical, ventilating, light, equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust, fume, gas, mist, vapors, spray.

5.3. Advice for fire-fighters

SDS Revision Date: 04/01/2020

In the event of fire, wear full protective clothing and NIOSH Approved Self-contained breathing apparatus with full face piece operated in the pressure demand or other positive pressure mode. Move container from fire area if it can be done without risk. Use water to keep fire exposed containers cool and disperse vapors.

ERG Guide No. 129

Section 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove sources of ignition, do not turn lights or unprotected electrical equipment on or off. In case of a major spill or spillage in a confined space evacuate the area and check that solvent vapor levels are below the Lower Explosive Limit before re-entering.

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Avoid sparks, flames, heat and smoking. Ventilate. Wear necessary protective equipment. Absorb in vermiculite, dry sand or earth and place into containers.

Small Spill: Use a non-combustible material like vermiculite, sand or earth to soak up product and place in a container for later disposal.

Section 7. Handling and storage

7.1. Precautions for safe handling

Handle containers carefully to prevent damage and spillage.

Keep in containers lightly closed in a cool, well ventilated place. Do not store with oxidizing agents or acids. Keep in the original container. Avoid direct sunlight

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Store in a cool dry area, away from heat, sparks and open flame.

Keep containers sealed when not in use.

Store out of direct sunlight.

Store in a cool dry place.

Incompatible materials: Store away from oxidizers and acids.

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

Section 8. Exposure controls / personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0000064-17-5 Ethanol		OSHA	TWA 1000 ppm (1900 mg/m3)
		ACGIH	No Established Limit
		NIOSH	TWA 1000 ppm (1900 mg/m3)
0000067-63-0	Isopropyl Alcohol	OSHA	TWA 400 ppm (980 mg/m3) STEL 500 ppm
		ACGIH	TWA: 200 ppm STEL: 400 ppm
		NIOSH	TWA 400 ppm (980 mg/m3) ST 500 ppm (1225 mg/m3)
0000107-98-2	1-Methoxy-2-propanol	OSHA	No Established Limit
		ACGIH	100 ppm STEL
		NIOSH	TWA 100 ppm (360 mg/m3) ST 150 ppm (540 mg/m3)
		OSHA	TWA 250 ppm (950 mg/m3)
		ACGIH	TWA: 100 ppm STEL: 200 ppm
		NIOSH	no established RELs
0009004-70-0	Cellulose Nitrate	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
0013463-67-7 Titanium dioxide		OSHA	TWA 15 mg/m3
		ACGIH	TWA: 10 mg/m3
		NIOSH	Footnote ca
800680-57-9	Rosin, Fumeric	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit

8.2. Exposure controls

Respiratory Atmospheric levels should be maintained below the exposure guideline. When respiratory protection

is required for certain operations, use an approved air-purifying respirator. The following should be

effective types of air purifying respirators: Organic vapor cartridge.

Eyes Wear safety eyewear, e.g. safety spectacles, goggles or visors to protect against the splash of

liquids.

Skin Overalls which cover the body, arms and legs should be worn. Skin should not be exposed. All parts

of the body should be washed after contact. Use gloves chemically resistant to this material when prolonged or frequently repeated contact could occur. Examples of preferred glove barrier materials include: Butyl rubber. Polyethylene/ethyl vinyl alcohol laminate ("PE/EVAL"). Examples of acceptable glove barrier materials include: Natural rubber ("latex"). Neoprene. Nitrile/butadiene

rubber ("nitrile" or "NBR"). Polyvinyl chloride ("PVC" or "vinyl"). Viton

Engineering Controls Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of

local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory

protection must be worn.

Other Work Practices Do not smoke, or drink in work area. Keep away from foodstuffs and beverages. Avoid contact with

eves and skin.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet.

Promptly remove soiled clothing and wash thoroughly before reuse.

SDS Revision Date: 04/01/2020

Safety Data Sheet F-123 All Except Red, Blue, Black, Brown

See section 2 for further details.

Section 9. Physical and chemical properties

Appearance Colored Liquid
Odor Sweet alcohol like
Odor threshold Not determined
pH Not Measured
Melting point / freezing point Not Measured
Initial boiling point and boiling range 82 C 160F

Flash Point 10-15C 50-60F Method (Setaflash)

Evaporation rate (Ether = 1) 1.0

Flammability (solid, gas) Not Applicable

Upper/lower flammability or explosive limits Lower Explosive Limit: 3.0

Upper Explosive Limit: 19.0

Vapor pressure (Pa)4.16 kPa Temperature (C) 20

Vapor Density >2

Relative Density0.810 g/mLSolubility in WaterNot MeasuredPartition coefficient n-octanol/water (Log Kow)Not MeasuredAuto-ignition temperatureNot MeasuredDecomposition temperatureNot MeasuredViscosity (cSt)Not Measured

VOC Content 65-75% Approximately 5.9 Lbs/gal

% Volatile 65-75%

9.2. Other informationNo other relevant information.

Section 10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

High temperatures and fires.

10.5. Incompatible materials

Store away from oxidizers and acids.

10.6. Hazardous decomposition products

None

Section 11. Toxicological information

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
1-Methoxy-2-propanol - (107-98-2)	4,277.00, Rat -	> 2,000.00, Rat -	No data	No data	No data
	Category: NA	Category: 4	available	available	available
Isopropyl Alcohol - (67-63-0)	5,840.00, Rat -	12,800.00, Rabbit	72.60, Rat -	No data	No data
	Category: NA	- Category: NA	Category: NA	available	available
Titanium dioxide - (13463-67-7)	>25,000.00, Rat -	No data	No data	6.82, Rat -	No data
	Category: NA	available	available	Category: NA	available
Rosin, Fumeric - (800680-57-9)	No data	No data	No data	No data	No data
	available	available	available	available	available
Ethanol - (64-17-5)	10,470.00, Rat -	17,100.00, Rabbit	124.70, Rat -	No data	No data
	Category: NA	- Category: NA	Category: NA	available	available
Acetic acid, 1-methylethyl ester - (108-21-4)	6,750.00, Rat -	20,000.00, Rabbit	17,129.60, Rabbit	No data	No data
	Category: NA	- Category: NA	- Category: NA	available	available
Cellulose Nitrate - (9004-70-0)	5,000.00, Mouse -	No data	No data	No data	No data
	Category: 5	available	available	available	available

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000064-17-5	Ethanol	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: Yes; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	A3
0000067-63-0	Isopropyl Alcohol	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
			A4
0000107-98-2	1-Methoxy-2-propanol	OSHA	Regulated Carcinogen: No
	N'I		Known: No; Suspected: No
			Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	A4
0000108-21-4	Acetic acid, 1-methylethyl ester	OSHA	Regulated Carcinogen: No

		NTP	Known: No; S	Suspected: No		
		IARC		Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		
		ACGIH	No Established Limit			
0009004-70-0	Cellulose Nitrate	OSHA	Regulated Carcinogen: No			
		NTP	Known: No;	Suspected: No		
		IARC	Group 1: No;	Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		
		ACGIH	No Establishe	d Limit		
0013463-67-7	Titanium dioxide	OSHA	Regulated Car	cinogen: No		
		NTP	Known: No;	Suspected: No		
		IARC	-	Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;		
		ACGIH				
800680-57-9	Rosin, Fumeric	OSHA	Regulated Car	-		
		NTP	Known: No;	Suspected: No		
		IARC	-	Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		
		ACGIH	No Establishe	d Limit		
Classification		Ca	itegory	Hazard Description		
Acute toxicity	(oral)			Not Applicable		
Acute toxicity	(dermal)			Not Applicable		
Acute toxicity	(inhalation)			Not Applicable		
Skin corrosio	n/irritation			Not Applicable		
Serious eye d	rious eye damage/irritation 2A		2A	Causes serious eye irritation.		
Respiratory so	ensitization			Not Applicable		
Skin sensitiza	tion			Not Applicable		
Germ cell mu	tagenicity			Not Applicable		
Carcinogenicity				Not Applicable		
Reproductive toxicity			Not Applicable			
STOT-single exposure			3	May cause drowsiness or dizziness.		
STOT-single exposure				Not Applicable		
STOT-repeated exposure				Not Applicable		
Aspiration hazard				Not Applicable		

Section 12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
1-Methoxy-2-propanol - (107-98-2)	6,812.00, Leuciscus idus	> 4,600.00, Daphnia magna	> 1,000.00 (96 hr), Pseudokirchneriella subcapitata
Isopropyl Alcohol - (67-63-0)	10,000.00, Pimephales promelas	Not Available	Not Available

Titanium dioxide - (13463-67-7)	294.00, Oryzias latipes	501.00, Daphnia magna	101.00 (72 hr), Pseudokirchneriella subcapitata
Rosin, Fumeric - (800680-57-9)	Not Available	Not Available	Not Available
Ethanol - (64-17-5)	15,400.00, Lepomis macrochirus	10,001.00, Daphnia magna	17.921 (96 hr), Ulva pertusa
Acetic acid, 1-methylethyl ester - (108-21-4)	Not Available	Not Available	Not Available
Cellulose Nitrate - (9004-70-0)	Not Available	Not Available	579.00 (96 hr), Pseudokirchneriella subcapitata

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

Section 13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

Section 14. Transport information

DOT (Domestic Surface IMO / IMDG (Ocean ICAO/IATA **Transportation**) **Transportation**) **14.1. UN number** UN1210 UN1210 UN1210 14.2. UN proper Printing ink Printing ink Printing ink shipping name **DOT Hazard Class:** 3 **IMDG:** 3 Air Class: 3 14.3. Transport hazard **DOT Label:** 3 **Sub Class:** Not Applicable Packing Instruction: Cargo Only - 364, class(es) EmS: F-E, S-D Passenger -353 14.4. Packing group II II II

14.5. Environmental hazards

IMDG Marine Pollutant: No

14.6. Special precautions for user

No further information

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

Section 15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are

represented. All components of this material are either listed or exempt from listing on the TSCA

Inventory.

NFPA Rankings:



US EPA Tier II Hazards

Sudden Release of Pressure: No

Reactive: No

Fire: Yes

Immediate (Acute): Yes
Delayed (Chronic): No

Note: Ethanol (Ethyl alcohol) has been placed on the California Proposition 65 Cancer and Developmental Lists when in alcoholic beverages.

EPCRA 311/312 Chemicals and RQs:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

Ethanol

Isopropyl Alcohol

Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

New Jersey RTK Substances (>1%):

1-Methoxy-2-propanol

Acetic acid, 1-methylethyl ester

Cellulose Nitrate

Ethanol

Isopropyl Alcohol

Titanium dioxide

Pennsylvania RTK Substances (>1%):

SDS Revision Date: 04/01/2020

1-Methoxy-2-propanol
Acetic acid, 1-methylethyl ester
Cellulose Nitrate
Ethanol
Isopropyl Alcohol

Section 16. Other information

SDS Revision Date 04/01/2020

Titanium dioxide

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.

H226 Flammable liquid and vapor.

H228 Flammable solid.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

This product is RoHS and REACH compliant. It does not contain any of the RoHS listed substances. It does not contain any chemical from the candidate list of Substances of Very High Concern (SVHC), Annex XIV, or Annex XVII of Reach.

This information is based on our present knowledge. However, it does not constitute a guarantee for any specific product properties.

Carco urges the recipient of this SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. The use of this product is beyond the control Carco or its distributor, therefore, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product.

End of Document